

## Emkarate<sup>®</sup> RL220H

### Typical Properties Data Sheet

#### Product Description:

Emkarate RL220H is an ISO VG 220 synthetic polyol ester (POE) lubricant formulated specifically for use in refrigeration and air-conditioning compressors using HFC refrigerants. This product provides effective wear protection for steel and aluminium surfaces for increased system life and improved efficiency and is suitable for both initial fill and service fill. The combination of low temperature characteristics and unparalleled chemical and thermal stability enable the use of Emkarate RL220H over a wide operating temperature range.

Analysis	Method	Typical Value
Viscosity @ 40°C (cSt)	ASTM D445	219
Viscosity @ 100°C (cSt)	ASTM D445	19.2
Viscosity Index	ASTM D2270	100
Pour Point (°C)	ASTM D97	-25
Density @ 20°C (g/ml)	ASTM D1298	0.975
Flash Point COC (°C)	ASTM D92	287
Acid Value (mg KOH/g)	ASTM D974	0.02
Colour (Hazen units)	ISO 2211	100
Water (ppm)	ASTM 6304	20
Miscibility (Low °C) 10% Lube in R134a	In House	-18
Miscibility (High °C) 10% Lube in R134a	In House	>80
Hydroxyl Value (mg KOH/g)	ASTM E326	4

*These values are not intended for use in preparing specifications.  
Additional technical information is available upon request.*

#### North & South America

The Lubrizol Corporation  
2300 James Savage Rd.  
Midland, MI 48642, USA  
Phone: 989-496-3780  
Email: sales@cpifluideng.com

#### Europe, Middle East & Africa

Lubrizol Limited  
Pavilion One, Belasis Court  
Greenwood Road  
Stockton-on-Tees  
TS23 4AZ, UK  
Phone: +44 1642 565266  
Email: euafricamesales@cpifluideng.com

#### Asia-Pacific

Lubrizol Southeast Asia (Pte) Ltd  
44 Tanjung Penjuru  
Singapore 609032  
Phone: +65-66638 684  
Email: asiasales@cpifluideng.com

[www.emkarateRL.com](http://www.emkarateRL.com)

[www.cpifluideng.com](http://www.cpifluideng.com)



**Lubrizol**

CPI Fluid Engineering is a Division of The Lubrizol Corporation